

STORVITE

Manufacturers and installers of the EPPOGRAN™ range of resin flooring

Coshh Assessment Sheet EPPOGRAN QUARTZ EPOXY SCREED

Substance	Epoxy resin & amine hardeners Hydrocarbon solvents
Use/Where found	Specialist floor coatings to lift cars
Hazards	Flammable materials – solvent vapours Irritant to skin and eyes Corrosive, acidic Fire hazard Poisonous – Ingestion and skin absorption may cause liver damage
Control Measures	Use barrier cream. Wash off any contamination with mild detergent and hot water, not solvent Change and dispose of contaminated coating immediately Wash hands after handling No smoking, always ventilate areas of application No naked flames Ensure all containers are kept dry and sealed prior to use Always wear protective clothing, gloves and eye shield
First Aid	Eye: Irrigate well with water only, seek medical aid Skin: Wash off with soap and hot water, rinse well Ingestion: Wash out mouth with WATER only, seek medical aid
Medical Aid	In case of accident/contamination seek medical aid immediately
Storage	Keep dry in sealed containers. Use physical barriers whilst installing
Spillage	Any spillage must be cleaned up before the product is cured and the spoils disposed of safely

Storvite Flooring Limited

30 Armstrong Road, Benfleet, Essex, SS7 4PW

Tel: 01268 795511 Fax: 01268 566117

Web: www.storvite.com